

Suzuki GSX-R1000 (03-04)

Bike Specific Install Notes and Tips

This is an aftermarket product that fits up different than the stock components, therefore, the installer may be required to set up components and to route lines in the "best way possible", which may not always be listed on this "Bike Specific" installation sheet. In any case, the installation must allow the handlebars to reach both steering stops, without pulling taught or kinking any lines, and without damaging any part of the motorcycle

Important Installation Considerations

Though longer lines are available, Stock throttle and clutch can be re-routed to reach the highest setting.

Special Kit Requirements/Installation Tips

1. Contact - Slight fairing contact is ok as long as the steering stops can be reached without damaging the fairing
2. Zip ties or brackets holding excess electrical lines will need to be cut or removed to free up extra length.

Handlebar Positioning

1. When the bars are in the down position, with the wheel straight, the clamps should be rotated so the handlebar risers are at approximately the 10 and 2 - O'Clock positions(as the rider is looking down at the top of the fork tubes) This will allow clearance with fairing side pieces as you turn stop to stop.
2. When the bars are in the up position, with the wheel straight, the clamps should be rotated so the handlebar risers are at approximately the 7 and 5 - O'Clock positions(as the rider is looking down at the top of the fork tubes) This will allow clearance with the upper fairing and windshield as you turn stop to stop.

Line Routing

1. Throttle Lines - Stock length - route behind the right fork tube
2. Throttle Lines - Longer than stock - route as stock
3. Clutch Line - Free line from bracket and routed for best length

Recommended Riser Trim Length

1. 6.5" Riser Length = Trim Number 11

Recommended parts and replacement lines

1. Suzuki GSX-R1000 (01-04) Stock+50mm length Clutch Line. Part Number- 07-0793. Order from ConvertiBARS
2. Suzuki GSX-R1000 (01-04) Stock+75mm length Throttle Lines. Part Numbers X-621, X-622. Order from ConvertiBARS
3. Hydraulic Brake Line Top Fitting - 90 degree face to the side
4. Hydraulic Brake Line = Stock + 5"
5. Cable Clutch Line - Stock + 2"

Up & Back



Down and Foreword

