

Suzuki GSX-R1000 (05-06)

Bike Specific Install Notes and Tips

This is an aftermarket product that fits up different than the stock components, therefore, the installer may be required to set up components and to route lines in the "best way possible", which may not always be listed on this "Bike Specific" installation sheet. In any case, the installation must allow the handlebars to reach both steering stops, without pulling taught or kinking any lines, and without damaging any part of the motorcycle

Important Installation Considerations

Special Kit Requirements/Installation Tips

1. Contact - Slight fairing contact is ok as long as the steering stops can be reached without damaging the fairing
2. Trimming - Depending on rise and preference, trimming the handlebar length will allow more rise
3. Moving - Moving the clutch lever, and brake lever toward the center of the motorcycle will allow greater upper fairing/windshield clearance
4. Fairing spacer pack recommended to lift the fairing for more rise.

Line Routing

1. Brake Line - Ensure line(s) and top fitting position does not interfere with instrument panel, riser, Cyclops Clamp, and or brake lever.
2. Throttle Lines - Stock Length - Stock Routing
3. Electrical Lines to be freed from their brackets and or Zip Ties, and run on the rider's side of the forks
4. Clutch Line - Longer than stock - route as stock

Recommended Riser Trim Length

1. 6.5" Riser Length = Trim Number 11

Recommended parts and replacement lines

1. Suzuki GSX-R1000 (05-06) Stock+50mm length Clutch Line(Part Number- 07-0910. Order from ConvertiBARS)
2. Suzuki GSX-R1000 (05-06) Stock+75mm length Throttle Lines. Part Numbers 07-0955, 07-0957. Order from ConvertiBARS
3. Hydraulic Brake Line Top Fitting - 000(Straight)
4. Hydraulic Brake Line = Stock + 5"
5. Throttle Lines - Ok rerouted
6. Throttle Lines - Stock + 2"

