

Suzuki GSX-R600 (00-03)

Bike Specific Install Notes and Tips

This is an aftermarket product that fits up different than the stock components, therefore, the installer may be required to set up components and to route lines in the "best way possible", which may not always be listed on this "Bike Specific" installation sheet. In any case, the installation must allow the handlebars to reach both steering stops, without pulling taught or kinking any lines, and without damaging any part of the motorcycle

Important Installation Considerations

In order to get more than about 2 inches of rise, some windshield and fairing trimming may be required

Restrictions

1. Upper fairing and or windshield can be trimmed for more rise.

Line Routing

1. Electrical Lines to be freed from their brackets and or Zip Ties, and run on the rider's side of the forks
2. Choke/Throttle advance line - Route behind the left fork tube

Recommended Riser Trim Length

1. 6.5" Riser Length = Trim Number 11

Recommended parts and replacement lines

1. Suzuki GSX-R600&750 (00-03) Stock+50mm length Clutch Line. Part Number-07-0793. Order from ConvertiBARS
2. Suzuki GSX-R600 (01-03) Stock+75mm length Throttle Lines. Part Numbers X-621, X-622. Order from ConvertiBARS.
3. Hydraulic Brake Line Top Fitting - 90 degree face to the side
4. Hydraulic Brake Line = Stock + 5"
5. Cable Clutch Line - Stock + 2"