

Suzuki GSX-R750 (00-03)

Bike Specific Install Notes and Tips

This is an aftermarket product that fits up different than the stock components, therefore, the installer may be required to set up components and to route lines in the "best way possible", which may not always be listed on this "Bike Specific" installation sheet. In any case, the installation must allow the handlebars to reach both steering stops, without pulling taught or kinking any lines, and without damaging any part of the motorcycle

Important Installation Considerations

In order to get more than about 2 inches of rise, some windshield and fairing trimming may be required

Special Kit Requirements/Installation Tips

1. Contact - Slight fairing contact is ok as long as the steering stops can be reached with out damaging the fairing
2. Zip ties or brackets holding excess electrical lines will need to be cut or removed to free up extra length.
3. Moving - Moving the clutch lever, and brake lever toward the center of the motorcycle will allow greater upper fairing/windshield clearance

Restrictions

1. Upper fairing and or windshield can be trimmed for more rise.

Line Routing

1. All longer lines routed as stock.
2. Throttle Lines - Stock length - route behind the right fork tube
3. Electrical Lines to be freed from their brackets and or Zip Ties, and run on the rider's side of the forks
4. Clutch Line - Free line from bracket and routed for best length
5. Clutch Line - Stock Length - Route behind fork tube
6. Clutch Line - Longer than stock - route as stock

Recommended Riser Trim Length

1. 6.5" Riser Length = Trim Number 11

Recommended parts and replacement lines

1. Suzuki GSX-R600&750 (00-03) Stock+50mm length Clutch Line. Part Number- 07-0793. Order from ConvertiBARS
2. Suzuki GSX-R750 (00-03) Stock+75mm length Throttle Lines. Part Numbers X-621, X-622. Order from ConvertiBARS.
3. Hydraulic Brake Line Top Fitting - 90 degree face to the side
4. Hydraulic Brake Line = Stock + 5"
5. Throttle Lines - Ok rerouted
6. Throttle Lines - Stock + 2"

7. Cable Clutch Line - Ok rerouted

8. Cable Clutch Line - Stock + 2"

