

Yamaha FZ6

Bike Specific Install Notes and Tips

This is an aftermarket product that fits up different than the stock components, therefore, the installer may be required to set up components and to route lines in the "best way possible", which may not always be listed on this "Bike Specific" installation sheet. In any case, the installation must allow the handlebars to reach both steering stops, without pulling taught or kinking any lines, and without damaging any part of the motorcycle

Important Installation Considerations

Fairing Causes restrictions to positioning

Special Kit Requirements/Installation Tips

1. Zip ties or brackets holding excess electrical lines will need to be cut or removed to free up extra length.
2. Moving - Moving the clutch lever, and brake lever toward the center of the motorcycle will allow greater upper fairing/windshield clearance

Restrictions

1. Fairing side pieces or intake ducts interfere with the riser when rotating the Cyclops Clamps. Raising the handlebar so the riser is above the fairing side pieces before rotating the Cyclops clamps will solve this restriction. Trimming the fairing side pieces could also increase convertibility.

Line Routing

1. Throttle lines - Stock Length - Route below the brake lever
2. Throttle Lines - Stock length - route behind the right fork tube

Recommended Riser Trim Length

1. 8.0" Riser Length = No Trimming

Recommended parts and replacement lines

1. All Stock Lines are long enough for documented rise

